



UV-1200

The Manitoba | Purifier

Description


The UV-1200 is a robust, high quality ultra-violet sterilizer designed for the disinfection of drinking water in the larger house where there is a 1" line, at a flow range between 13.2 and 33 GPM (50 - 125 LPM). Typically installed at the point of entry, it can treat municipal water as well as ground water from drilled or dug wells, and surface water from lakes, ponds or rivers. Other applications for this sterilizer are for the purification of drinking and process water in small commercial applications.

This UV sterilizer contains a low-pressure, high output UV lamp in a 304L stainless steel reaction chamber (also available in 316L). It comes with an electronic ballast that features a lamp-out alarm if there is no power to the lamp.

Combined with a Wyckomar filter set, this sterilizer is the centre piece of a complete water treatment system for the elimination of bacteria and viruses and reduction of taste and odour at the point of entry (see part # SYS1200-QD4E-1/2).

Additional features for this sterilizer can be ordered, such as a thermo-sensitive purge valve at the out port to prevent overheating in no-flow conditions, or volt-free contacts on the ballast for remote signaling.

The UV-1200 kills most harmful microbiological contaminants, such as viruses, bacteria and protozoa with a powerful UV disinfection dose that will inactivate the pathogens at a kill rate of 99.99% (log 4) or more (*Giardia*, *E. coli*, *Cryptosporidium*, *Vibrio cholerae*, *Legionella*, *Salmonella*, *Shigella*, *Streptococcus* and many others).



Applications

- ▶ Potable Water
- ▶ Whole House Water Treatment
- ▶ Small Commercial Applications
- ▶ Coffee Shops, Hair Salons, Doctor's Offices
- ▶ Pharmaceutical Manufacturing

Benefits


- ▶ Efficient Disinfection, Low Cost per Litre
- ▶ High UV Dose for Peace of Mind
- ▶ Easy Installation
- ▶ Extremely Simple to Use and Maintain
- ▶ Easy Lamp Replacement
- ▶ High Quality Stainless Steel Reaction Chamber
- ▶ Domed Quartz Sleeve with Single Seal
- ▶ Made in Canada



Flow Range:	50 - 125 litres per minute (13.2 - 33 GPM) 3,000 l (3.0m ³) - 7,500 l (7.5 m ³) /hour / 72 - 180 m ³ /day 792 - 1980 gallons/hour, 19,000 - 47,250 gallons/day
UV Dose Applied (95% UVT):	16 mJ/cm ² (16,000 μWsec/cm ²) @ 125 LPM / 33 GPM 30 mJ/cm ² (30,000 μWsec/cm ²) @ 68 LPM / 18 GPM 40 mJ/cm ² (40,000 μWsec/cm ²) @ 50 LPM / 13.2 GPM
Electrical:	110 Volt AC / 50 - 60 Hz (Part # P1200/QD4E-1) 240 Volt AC / 50 - 60 Hz (Part # P1200/QD4E-2)
Ballast:	Electronic Ballast w/ Lamp Out Alarm, Power LED, Count of Total Running Days on LCD Display (Resettable) Model RH51-800-95L (Wyckomar Part # 4-BE800-ECO)
Ballast Enclosure Rating:	IP64
Lamp Current:	0.75 A - 0.85 A / U-Out: 300 V / PF(λ): > 0.99% / THD: < 10%
Number of Lamps:	1 at 84 Watts, 800 mA (Part # RL-84/893T5) Low-Pressure UV
Optional UV Monitor:	Analog (Part # 4-UV/MS-1/2 V3) / Digital (Configuration Dependent)
Min/Max. Operating Temperature:	T _{min.} = 3 °C (37 °F), T _{max.} = 40 °C (104 °F)
Max. Operating Pressure:	125 psi - 8.6 bar
Plumbing:	1" MNPT In/Out
Chamber Material:	304L Stainless Steel (316L SS optional)
Shipping Size and Weight:	1 box 45x7x7 inches, 12 lbs / 5.5 kg

Specifications subject to change

Dose Chart



Additional Features / Configuration Options:

- Volt-Free (Dry) Contacts on Ballast for Remote Signaling
- Thermosensitive Purge Valve at Out Port for Overheat Protection
- Integrated Control Panel with Digital Touch Screen Display and Remote Access for Comprehensive System Management and for Capturing / Logging of Sensor and Operation Data
- Available w/ Sanitary Tri-Clamp Fittings

Important Considerations

This UV sterilizer assumes certain water quality parameters to be met for proper operation. If the source water does not meet the following criteria, pretreatment has to be considered:

Turbidity (Suspended Solids): Must be < 1 NTU at the time of disinfection. There must be a 5 micron or less sediment prefiltration system installed before the UV system.

Total Hardness (Sum of Calcium and Magnesium): Must be < 10 gpg (grains per gallon)

Iron: Must be < 0.3 ppm (parts per million)

Manganese: Must be < 0.05 ppm

This UV unit is available as complete system with appropriate pre-filtration (Part # SYS1200/QD4E-1/2) or as pre-assembled All-in-One System for 'plug-and-play' installation (Part # SYS-MD1004-1/2)